

2316HM

Contton Paper Tape

Technical Data

- Product Description**

2316HM is a contton paper carrier tape with resin adhesive double coated . It has a very high level of initial tack and good adhesion to a wide variety of sufaces.


- Key Features**

Excellent initial adhesion.
 Excellent resistance to high temperature.
 Good adhesion to film and plastic materials

- Application Ideas**

Adhesive to MARK,film,power switch,foam materials,fabric materials as well as plastic materials.

- Construction**



- Technical Data**

Test Item	Unit	Value	Test Method
Thickness	mm	0.16±0.02	—
Initial Adhesion	-	> 12#	GB/T4852,Ball tack. J.dow method at room temperature. Tape size: 100mm*150mm.
180° Peel Adhesion	gf/25mm	2800	180°peel strength to substrate at room temperature (30 min)
Holding Power	hrs	> 120	GB/7754,Tensile strength, tape size:25mm*25mm, loading: 1kg
Temperature Resistance	--	-20℃~80℃	—
Color	White		—
Release Liner	Paper Liner		—
Product Size	1.05m*50m		—

- Shelf Life & Storage Conditions**

Tape in roll form: Shelf life 12 months from the date of manufacture whe stored in original cartons at 20 °C and 50% relative humidity.

Ideal tape application temperature range is 21 °C to 38 °C.

Notes: The information contained in this data sheet is intended to assist you in designing with Incheng adhesive tape. The technical information and datas should be considered representative or typical only. It is not intended to and does not create any warranties,express or implied, including any warranty of merchantability or fitness for particular purpose or that the results shown on this data sheet will be achieved by user for a particular purpose.The user should determine the suitability of Incheng asdhesive tape for each application.

China Sole Agency

Servtek Materials Technology (Guangzhou) Co.,Ltd

Tel : (+86)20-38892652/38255282



Fax: (+86)20-38892205